

LANDSCAPE WALL | MURINO™ - CUTTING

Murino™

Wall Cutting Option 1: Cutting a wall unit that is installed in a place where texture is mating to one side and the other side has the return angle.



STEP 1: Measure the opening gap in your wall (8" shown in this example). Use a large unit (16" wide on long side) to create your cut piece. You will need to remove 8" from the middle of this unit.



STEP 2: Mark a center line on this unit. Next measure half the distance (4") and mark a parallel line on each side of the center line. This will be the 8" that you will need to remove.



STEP 3: Cut along the two outside lines you just marked and remove the center waste piece.



STEP 4: Pull the two outside pieces together along the cut side which will be used to fill the 8" opening gap within the wall.

Note: you may need to adjust how the pieces come together to minimize the visible cut ledge.



STEP 5: For stability and aesthetics, place cut units in the middle of the wall. Line up the cut sides on the textured faces to minimize any offset that may be visible.



STEP 6: Due to the removal of pin holes during the cutting process, these pieces will need to be secured with exterior grade concrete adhesive.

Wall Cutting Option 2: Cutting a wall unit that is installed in place where texture is mating to both sides. This will require 2 small units to achieve mating texture on both sides.



STEP 1: Measure the opening gap (7" shown). This will require a 3½" section each of 2 small units.



STEP 2: On each of the units, locate and mark the center line which will go through the center pin holes. Next, mark a second line at 3½ from textured edge as shown.



STEP 3: Cut along the 3½" marked line on each unit and remove the waste piece between.

(Continue by following **Steps 4-6** from Option 1.)

Cap Cutting: Capping units add that finishing touch to your wall and should naturally overhang the end by ½ inch.



STEP 1: Temporarily place capping units on finished wall to determine the amount of overhang.



STEP 2: Measure the overhang and subtract ½" (equals 5" in this example). This will be the distance that will need to be removed.



STEP 3: Mark a center line on the cap in the direction to be cut. Next, mark two additional lines 2½" on each side of center line. (2½" + 2½" = 5")



STEP 4: Cut along the two outside lines and remove the inner waste piece.



STEP 5: Pull the two pieces together to create what will fill the void in the wall capping.



STEP 6: For stability and aesthetics, place cut units in the middle of the wall capping and secure in place with exterior grade concrete adhesive.



Keystone Retaining Wall Systems LLC • A Contech Company
4444 West 78th Street • Minneapolis, MN 55435
(952) 897-1040 • www.keystonewalls.com

©2018 Keystone Retaining Wall Systems LLC

