



LANDSCAPE WALL | VERAZZO STONE®

Verazzo Stone®

Keystone's Verazzo Stone is a 1-piece system favored for its easy installation and unsurpassed natural stone aesthetic. Verazzo Stone is the perfect combination of rugged good looks, design versatility and strength; enhancing any landscape.



1-Piece Wall System



Unit Dimensions & Weights:

6" h x 16" / 12" w x 10 1/2" d; 68 lbs
(152mm x 406/305mm x 267mm; 31 kg)

Units/sq.ft: 1.7

Alignment Pins:

Two required per unit.



FEATURES & BENEFITS

Perfect For:

- Retaining walls up to 3' (0.9m)h.
- Both 1 and 2-sided project designs, including: fire pits, columns, free-standing walls and planters.
- Enhancing any outdoor setting with its natural stone beauty.

Unparalleled Simplicity

- Easy to install, single-unit system.
- Random-pattern aesthetics without a mixed pallet or multiple pieces.
- Keystone's proven pin connection system aids in unit alignment.

Exceptional Versatility

- Angled on both sides, providing different face lengths for tight fitting straight-line walls and radii at curves.
- Multiple pin positions allow for near vertical or positive setbacks.

Note: Unit color, dimensions, weight & availability varies by manufacturer.



LANDSCAPE WALL | VERAZZO STONE®

INSTALLATION INSTRUCTIONS



1. Prepare the Site

Start by digging a shallow trench 12" (305mm) deep by 24" (610mm) wide. Cut through and remove any sod, roots or large rocks. Place 6" (152mm) leveling pad of compacted sand or gravel in the trench to receive the first course of Verazzo Stone.



2. Set the Base Course

Place and level the first Verazzo Stone unit. Level each additional unit on the base course as you place it, making sure that the outside edges touch. *If your wall contains both straight and curved areas, start with a straight area and build into the curves. Complete the base course before proceeding to the second course.



3. Pin, Stack & fill

Starting with straight areas first, begin placing the second course. Center each Verazzo Stone unit over the pins on the joints of the course below in a running bond pattern as shown. Now proceed to the next layer, backfilling as you go. For drainage between units and behind the wall, clean gravel or crushed stone is recommended.

NOTES:

- *For straight line walls, unit faces can be alternated to create a more random look.
- **Cap units vary by region. Contact your local Keystone representative for product availability.

Capping: Complete your wall with the appropriate capping** units. With units dry and clean, use exterior grade construction adhesive on the top surface of the last course before applying cap units. Backfill and compact to finish grade.