

KEYSTONE VERAZZO STONE® DESIGN CHARTS




LTDS = 750 plf (10.9 kN/m) or Tal = 500 plf (7.3 kN/m)


DESIGN ASSUMPTIONS

- Moist weight of three soil types indicated is 120 lb./ft³ (19kN/m²).

GRAVITY WALL NEAR VERTICAL DETAIL



REINFORCED WALL NEAR VERTICAL DETAIL



Design Notes


For low (non-structural) landscape retaining walls, Verazzo Stone can be constructed as a non-reinforced gravity wall as shown in the chart below. This chart is for retaining walls in the “near vertical” option.

Note: use pins and construction adhesive at low border/
parapet walls.


GRAVITY WALLS (MAXIMUM UNREINFORCED WALL HEIGHT)				
MAX. HEIGHT*	NEAR VERTICAL		9.5° +/- BATTER	
	Level	3H:1V	Level	3H:1V
SAND / GRAVEL PHI = 34°	2'-3" (0.7m)	1'-9" (0.55m)	3'-3" (1.0m)	2'-9" (0.85m)
SILTY SAND PHI = 30°	1'-9" (0.55m)	1'-9" (0.55m)	2'-9" (0.85m)	2'-3" (0.7m)
SILT / LEAN CLAY PHI = 26°	1'-9" (0.55m)	1'-3" (0.4m)	2'-3" (0.7m)	1'-9" (0.55m)

*Height does not include 3" cap (.076M)

GRAVITY WALL SETBACK DETAIL 9.5°+ BATTER









REINFORCED WALL SETBACK DETAIL 9.5°+ BATTER









Design Charts

The following charts assume the use of a coated polyester geogrid with a minimum allowable design strength of:
LTDS = 750 plf (10.9 kN/m) or Tal = 500 plf (7.3 kN/m)

Silt/Lean Clay: $\phi=26^\circ$, $\gamma=120$ pcf (19kN/m³)

CASE 1	REINFORCED WALLS - (NEAR VERTICAL)								
	<p>LENGTH CONVERSION</p> <table border="1"> <tr><td>4'</td><td>1.2m</td></tr> <tr><td>5'</td><td>1.5m</td></tr> <tr><td>6'</td><td>1.8m</td></tr> <tr><td>7'</td><td>2.1m</td></tr> </table>  <p>H= 2.25' (0.7m) 3.25' (1.0m) 4.25' (1.3m) 5.25' (1.6m) 6.25' (1.9m)</p>	4'	1.2m	5'	1.5m	6'	1.8m	7'	2.1m
4'	1.2m								
5'	1.5m								
6'	1.8m								
7'	2.1m								
CASE 2	REINFORCED WALLS - (NEAR VERTICAL)								
	<p>LENGTH CONVERSION</p> <table border="1"> <tr><td>4'</td><td>1.2m</td></tr> <tr><td>5'</td><td>1.5m</td></tr> <tr><td>6'</td><td>1.8m</td></tr> <tr><td>7'</td><td>2.1m</td></tr> </table>  <p>H= 2.25' (0.7m) 3.25' (1.0m) 4.25' (1.3m) 5.25' (1.6m) 6.25' (1.9m)</p>	4'	1.2m	5'	1.5m	6'	1.8m	7'	2.1m
4'	1.2m								
5'	1.5m								
6'	1.8m								
7'	2.1m								
CASE 3	REINFORCED WALLS - (NEAR VERTICAL)								
	<p>LENGTH CONVERSION</p> <table border="1"> <tr><td>4'</td><td>1.2m</td></tr> <tr><td>5'</td><td>1.5m</td></tr> <tr><td>6'</td><td>1.8m</td></tr> <tr><td>7'</td><td>2.1m</td></tr> </table>  <p>H= 2.25' (0.7m) 3.25' (1.0m) 4.25' (1.3m) 5.25' (1.6m) 6.25' (1.9m)</p>	4'	1.2m	5'	1.5m	6'	1.8m	7'	2.1m
4'	1.2m								
5'	1.5m								
6'	1.8m								
7'	2.1m								

*FOR CONSTRUCTION OF NEAR VERTICAL BATTER (CENTER PIN HOLE), CONSTRUCT WITH POSITIVE BATTER BY TILTING UNITS BACK TOWARDS FILL ON LEVELING PAD. ELEVATION DROP ALONG THE 10" WIDTH OF THE BLOCK TO BE 3/8".




CASE 1	REINFORCED WALLS - (9.5° ± SETBACK)								
	<p>LENGTH CONVERSION</p> <table border="1"> <tr><td>4'</td><td>1.2m</td></tr> <tr><td>5'</td><td>1.5m</td></tr> <tr><td>6'</td><td>1.8m</td></tr> <tr><td>7'</td><td>2.1m</td></tr> </table>  <p>H= 2.25' (0.7m) 3.25' (1.0m) 4.25' (1.3m) 5.25' (1.6m) 6.25' (1.9m)</p>	4'	1.2m	5'	1.5m	6'	1.8m	7'	2.1m
4'	1.2m								
5'	1.5m								
6'	1.8m								
7'	2.1m								
CASE 2	REINFORCED WALLS - (9.5° ± SETBACK)								
	<p>LENGTH CONVERSION</p> <table border="1"> <tr><td>4'</td><td>1.2m</td></tr> <tr><td>5'</td><td>1.5m</td></tr> <tr><td>6'</td><td>1.8m</td></tr> <tr><td>7'</td><td>2.1m</td></tr> </table>  <p>H= 2.25' (0.7m) 3.25' (1.0m) 4.25' (1.3m) 5.25' (1.6m) 6.25' (1.9m)</p>	4'	1.2m	5'	1.5m	6'	1.8m	7'	2.1m
4'	1.2m								
5'	1.5m								
6'	1.8m								
7'	2.1m								
CASE 3	REINFORCED WALLS - (9.5° ± SETBACK)								
	<p>LENGTH CONVERSION</p> <table border="1"> <tr><td>4'</td><td>1.2m</td></tr> <tr><td>5'</td><td>1.5m</td></tr> <tr><td>6'</td><td>1.8m</td></tr> <tr><td>7'</td><td>2.1m</td></tr> </table>  <p>H= 2.25' (0.7m) 3.25' (1.0m) 4.25' (1.3m) 5.25' (1.6m) 6.25' (1.9m)</p>	4'	1.2m	5'	1.5m	6'	1.8m	7'	2.1m
4'	1.2m								
5'	1.5m								
6'	1.8m								
7'	2.1m								

• The information provided herein is for preliminary design use only. A qualified engineer should be consulted for design and analysis of structures. Keystone Retaining Wall Systems LLC assumes no liability for the improper use of this information. *Information on specific geogrids is available from the geogrid manufacturer.




Design Charts

The following charts assume the use of a coated polyester geogrid with a minimum allowable design strength of:
 LTDS = 750 plf (10.9 kN/m) or Tal = 500 plf (7.3 kN/m)

Silty Sand: $\phi=30^\circ$, $\gamma=120$ pcf (19kN/m³)









*FOR CONSTRUCTION OF NEAR VERTICAL BATTER (CENTER PIN HOLE), CONSTRUCT WITH POSITIVE BATTER BY TILTING UNITS BACK TOWARDS FILL ON LEVELING PAD. ELEVATION DROP ALONG THE 10" WIDTH OF THE BLOCK TO BE 3/8".









• The information provided herein is for preliminary design use only. A qualified engineer should be consulted for design and analysis of structures. Keystone Retaining Wall Systems LLC assumes no liability for the improper use of this information. *Information on specific geogrids is available from the geogrid manufacturer.

The following charts assume the use of a coated polyester geogrid with a minimum allowable design strength of:
LTDS = 750 plf (10.9 kN/m) or Tal = 500 plf (7.3 kN/m)

Sand/Gravel: $\phi=34^\circ$, $\gamma=120$ pcf (19kN/m³)

CASE 1	REINFORCED WALLS - (NEAR VERTICAL)								
	<p>LENGTH CONVERSION</p> <table border="1"> <tr><td>4'</td><td>1.2m</td></tr> <tr><td>5'</td><td>1.5m</td></tr> <tr><td>6'</td><td>1.8m</td></tr> <tr><td>7'</td><td>2.1m</td></tr> </table> 	4'	1.2m	5'	1.5m	6'	1.8m	7'	2.1m
4'	1.2m								
5'	1.5m								
6'	1.8m								
7'	2.1m								
CASE 2	REINFORCED WALLS - (NEAR VERTICAL)								
	<p>LENGTH CONVERSION</p> <table border="1"> <tr><td>4'</td><td>1.2m</td></tr> <tr><td>5'</td><td>1.5m</td></tr> <tr><td>6'</td><td>1.8m</td></tr> <tr><td>7'</td><td>2.1m</td></tr> </table> 	4'	1.2m	5'	1.5m	6'	1.8m	7'	2.1m
4'	1.2m								
5'	1.5m								
6'	1.8m								
7'	2.1m								
CASE 3	REINFORCED WALLS - (NEAR VERTICAL)								
	<p>LENGTH CONVERSION</p> <table border="1"> <tr><td>4'</td><td>1.2m</td></tr> <tr><td>5'</td><td>1.5m</td></tr> <tr><td>6'</td><td>1.8m</td></tr> <tr><td>7'</td><td>2.1m</td></tr> </table> 	4'	1.2m	5'	1.5m	6'	1.8m	7'	2.1m
4'	1.2m								
5'	1.5m								
6'	1.8m								
7'	2.1m								

*FOR CONSTRUCTION OF NEAR VERTICAL BATTER (CENTER PIN HOLE), CONSTRUCT WITH POSITIVE BATTER BY TILTING UNITS BACK TOWARDS FILL ON LEVELING PAD. ELEVATION DROP ALONG THE 10" WIDTH OF THE BLOCK TO BE 3/8".

CASE 1	REINFORCED WALLS - (9.5° ± SETBACK)								
	<p>LENGTH CONVERSION</p> <table border="1"> <tr><td>4'</td><td>1.2m</td></tr> <tr><td>5'</td><td>1.5m</td></tr> <tr><td>6'</td><td>1.8m</td></tr> <tr><td>7'</td><td>2.1m</td></tr> </table> 	4'	1.2m	5'	1.5m	6'	1.8m	7'	2.1m
4'	1.2m								
5'	1.5m								
6'	1.8m								
7'	2.1m								
CASE 2	REINFORCED WALLS - (9.5° ± SETBACK)								
	<p>LENGTH CONVERSION</p> <table border="1"> <tr><td>4'</td><td>1.2m</td></tr> <tr><td>5'</td><td>1.5m</td></tr> <tr><td>6'</td><td>1.8m</td></tr> <tr><td>7'</td><td>2.1m</td></tr> </table> 	4'	1.2m	5'	1.5m	6'	1.8m	7'	2.1m
4'	1.2m								
5'	1.5m								
6'	1.8m								
7'	2.1m								
CASE 3	REINFORCED WALLS - (9.5° ± SETBACK)								
	<p>LENGTH CONVERSION</p> <table border="1"> <tr><td>4'</td><td>1.2m</td></tr> <tr><td>5'</td><td>1.5m</td></tr> <tr><td>6'</td><td>1.8m</td></tr> <tr><td>7'</td><td>2.1m</td></tr> </table> 	4'	1.2m	5'	1.5m	6'	1.8m	7'	2.1m
4'	1.2m								
5'	1.5m								
6'	1.8m								
7'	2.1m								

• The information provided herein is for preliminary design use only. A qualified engineer should be consulted for design and analysis of structures. Keystone Retaining Wall Systems LLC assumes no liability for the improper use of this information. *Information on specific geogrids is available from the geogrid manufacturer.